



STRAIGHT TUBE - SAE							
CODE	CONNECTIONS		SPHERE PASSAGE	PS	TS		KV
	DN		Ø	bar	°C		DDP=1bar (m³/h)
	Di (mm)	SAE	mm				
REF1.1.S.A.010.B038	-	3/8" F	10	120	-40	+150	2,7
REF1.1.S.A.012.B127	-	1/2" F					2,7

Valvola a sfera 2 vie con Schrader - SAE Flare Femmina / 2 way Ball valves with Schrader - SAE Flare Female connections
2 Wege Kugelventile mit Schrader - Bördelanschlüsse Innen / Vanne à bille 2 voies avec Schrader - SAE Flare Femelle



CODE	CONNECTIONS		SPHERE PASSAGE	PS	TS		KV
	DN		Ø	bar	°C		DDP=1bar (m³/h)
	ODS (mm)	NPT (inches)	mm				
REF1.1.N.P12.015.120	15mm	1/2"	15	120	-40	+150	12,5
REF1.1.N.P12.016.120	16mm	1/2"					13
REF1.1.N.P12.018.120	18mm	1/2"					13
REF1.1.N.P01.022.120	22mm	1"					24

Valvola a sfera 2 vie senza Schrader - Connessione INOX - NPT / ODS-NPT 2 way Ball valves without Schrader - Steel - NPT connection ODS-NPT 2 Wege Kugelventile ohne Schrader - Stahl lötlanschlüsse - NPT / Vanne à bille 2 voies sans Schrader - Connexion de acier - NPT



CODE	CONNECTIONS		SPHERE PASSAGE	PS	TS		KV
	DN		Ø	bar	°C		DDP=1bar (m³/h)
	ODS (mm)	Butt welding mm	mm				
REF1.1.N.A.010K65120	10	10	8	120	-40	+150	2,40
REF1.1.N.A.012K65120	12	12					2,70
REF1.1.N.B.016K65120	16	16	15				13
REF1.1.N.B.018K65120	18	18					14
REF1.1.N.C.022K65120	22	22	19				24
REF1.1.N.D.028K65120	28	28	22				40
REF1.1.N.E.035K65120	35	35	28				67,3
REF1.1.N.F.042K65120	42	42	38				98

Valvole 2 vie NPT / 2 Way Ball Valves NPT / 2 Wege Kugelventile NPT / Vannes 2 voies NPT



NPT BALL VALVES M/F							
CODE	CONNECTIONS		SPHERE PASSAGE	PS	TS		KV
	NPT		Ø	bar	°C		DDP=1bar (m³/h)
	M	F	mm				
REF1.1.P.B.012.1.N120	1/2"	1/2"	15	120	-40	+150	13
REF1.1.P.C.001.1.N120	1"	1"	19				24

Valvole a sfera 2 vie senza Schrader - Connessione INOX - CuFe2P / 2 way Ball valves without Schrader - Steel - CuFe2P connection / 2 Wege Kugelventile ohne Schrader - Stahl und CuFe2P lötlanschlüsse / Vannes à bille 2 voies sans Schrader - Connexion de acier et CuFe2P

NPT BALL VALVES M/F							
CODE	CONNECTIONS		SPHERE PASSAGE	PS	TS	KV	DDP=1bar (m ³ /h)
	SAE	SAE	Ø				
	inches	inches	mm	bar	°C		
REF1.1.N.A.006.4.120	1/4"	1/4"	8	52	-40	+150	0,8
REF1.1.N.A.010.4.120	3/8"	3/8"					2,4

Valvola a sfera 2 vie senza Schrader - SAE Flare Maschio / 2 way Ball valves without Schrader - SAE Flare Male / 2 Wege Kugelventile ohne Schrader - Bördelanschlüsse Aussen / Vanne à bille 2 voies sans Schrader - SAE Flare Mâle

CODE	CONNECTIONS		SPHERE PASSAGE	PS	TS	KV	DDP=1bar (m ³ /h)
	STAINLESS STEEL		Ø				
	Di (mm)	SAE	mm	bar	°C		
REF1.1.N.A.I10.F14S	10	1/4" M	8	120	-40	+150	2,4
REF1.1.N.A.I12.F14S	12	1/4" M					2,7

Valvola a sfera 2 vie senza Schrader - Connessione INOX - SAE Flare Maschio / ODS-NPT 2 way Ball valves without Schrader - Steel Connection - SAE Flare Male / ODS-NPT 2 Wege Kugelventile ohne Schrader - Sthal lötanschlüsse - Bördelanschlüsse Aussen / Vanne à bille 2 voies sans Schrader - Connexion de acier et SAE Flare Mâle

CODE	CONNECTIONS		SPHERE PASSAGE	PS	TS	KV	DDP=1bar (m ³ /h)
	CuFe2P - K65		Ø				
	ODS (mm)	SAE	mm	bar	°C		
REF1.1.N.A.006.F14S	6	1/4" M	8	120	-40	+150	1
REF1.1.N.A.014.F14S	1/4"	1/4" M					1
REF1.1.N.A.K38.F14S	3/8	1/4" M					2,4
REF1.1.N.A.K10.F14S	10	1/4" M					2,4
REF1.1.N.A.K12.F14S	1/2	1/4" M					2,7
REF1.1.N.A.K127.F14S	12	1/4" M					2,7

Valvole a sfera 2 vie senza Schrader / Connessione CuFe2P - SAE Flare Maschio / 2 way Ball valves without Schrader / CuFe2P connection - SAE Flare Male / 2 Wege Kugelventile ohne Schrader / CuFe2P lötanschlüsse und Bördelanschlüsse Aussen / Vannes à bille 2 voies sans Schrader / Connexion de CuFe2P et SAE Flare Mâle

CODE	CONNECTIONS		SPHERE PASSAGE	PS	TS	KV	DDP=1bar (m ³ /h)
	STAINLESS TEEL		Ø				
	Di (mm)	GAS	mm	bar	°C		
REF1.1.N.V.I10.FG38	10	3/8 F	10	120	-40	+150	2,4
REF1.1.N.V.I12.FG38	12	3/8 F	10				2,7

Valvola a sfera 2 vie senza Schrader - Connessione INOX - SAE Flare Femmina / 2 way Ball valves without Schrader - Steel Connection - SAE Flare Female connections / 2 Wege Kugelventile ohne Schrader - Sthal lötanschlüsse - Bördelanschlüsse Innen / Vanne à bille 2 voies sans Schrader - Connexion de acier et SAE Flare Femelle

CODE	CONNECTIONS		SPHERE PASSAGE	PS	TS	KV	DDP=1bar (m ³ /h)
	CuFe2P - K65		Ø				
	Di (mm)	GAS	mm	bar	°C		
REF1.1.N.V.K38.FG38	3/8	3/8 F	10	120	-40	+150	2,4
REF1.1.N.V.K10.FG38	10	3/8 F					2,4
REF1.1.N.V.K127.FG38	1/2	3/8 F					2,7
REF1.1.N.V.K12.FG38	12	3/8 F					2,7

Valvola a sfera 2 vie senza Schrader - Connessione CuFe2P - SAE Flare Femmina / 2 way Ball valves without Schrader - CuFe2P Connection - SAE Flare Female connections / 2 Wege Kugelventile ohne Schrader - S CuFe2P lötanschlüsse - Bördelanschlüsse Innen / Vanne à bille 2 voies sans Schrader - Connexion de CuFe2P et SAE Flare Femelle

