



REF-METER-OCTA-PLUS

Item Number 4681823

The REF-METER-OCTA-PLUS is the optimal supplement for autonomous filling of refrigeration systems. The control box of the REF-METER-OCTA or the OCTA-WIRELESS is programmed to the desired filling level and pushed into the holder. When the fill level is reached, the solenoid valve closes automatically.

- Reliable filling of refrigeration system
- Prevents overfilling of refrigerant cylinders

Technical Data

Material	Brass ABS Neoprene (CR)
Colour	yellow (RAL 1023) green (RAL 6026)
Standards	EN 55022: 2006 + A1: 2007 EN 55024: 1998 + A1: 2001 + A2: 2003
RoHS Conformity	1
RoHS Conformity	Yes
Connector A	1/4" SAE Outside thread
Connector B	1/4" SAE Outside thread
Working Pressure	34 bar
Temperature Range	0 - 50 °C
Battery	4 x AA
Operating Hours	200 h
Scope of Supply	Batteries Instruction manual
Packaging	Cardboard box

Accessories

Acknowledged globally



4688292	REFSCALE	Electronic charging scale, capacity: 110 kg Accuracy: +/- 0.05% or 10g
4679462	REF-METER-OCTA	Electronic charging scale, capacity: 110 kg Accuracy: +/- 0.5%, Resolution: 2 g
4686663	OCTA-WIRELESS	Wireless electronic charging scale, capacity: 110 kg Accuracy: +/- 0.5%, Resolution: 2 g