

FLÖDESVAKTER

Kompakta modeller



Serie SN 450

Gänga G1/2

AC 230 V • 115 V

Reläutgång



Design	G1/2 • L= 31 mm		G1/2 • L= 48 mm	
Dimensioner				
Mätområde	[cm/s] Vatten 1...150 / Olja 3...300			
Utgång				
Sensör längd L	[mm] 31	31	48	48
Gänga	G1/2	G1/2	G1/2	G1/2
ID-No.	P11113	P11114	P11074	P11076
Typ	SN 450-A4-WR1	SN 450-A4-WR2	SN 450/1-A4-WR1	SN 450/1-A4-WR2
Matningsspänning	[V] 115 AC ±15%	230 AC ±15%	115 AC ±15%	230 AC ±15%
Strömförbrukning	[mA] 60	30	60	30
Brytspänning	[V]	250 AC / 60 DC		
Brytström	[mA]	4 A AC / 4 A DC		
Max. bryteffekt		1000 VA / 60 W		
Omgivande temperatur	[°C]	-20...+70		
Medietemperatur	[°C]	-20...+80		
Temperaturgradient	[K/min]	250		
Starttid typ.	[s]	8 (2...15)		
Reaktionstid typ.	[s]	2 (1...13)		
Kompressionstålighet	[bar]	100		
Sensormaterial	AISI 316 Ti • andra material på begäran			
Material i höljet	PBT			
Visning av flöde	LED			
Skyddsklass	[EN 60529]	IP 67		
Anslutning	2 m PVC-kabel, 5x0.5 mm ²			