

Model: ZXDE-050E-TFD

Refrigerant: R404A Dew Point

S.I.

Evaporating Temperature	t	-10,00	°C
Annual electricity consumption	Q	16265	kWh/y
Seasonal energy performance ratio	SEPR	3,41	

Parameters at full load and ambient temperature 32°C

Capacity (rated)	P _A	9,03	kW
Power Input (rated)	D _A	4,02	kW
COP (rated)	COP _A	2,24	

Parameters at part load and ambient temperature 25°C

Capacity (declared)	P _B	9,92	kW
Power Input (declared)	D _B	3,63	kW
COP (declared)	COP _B	2,74	

Parameters at part load and ambient temperature 15°C

Capacity (declared)	P _C	11,14	kW
Power Input (declared)	D _C	3,10	kW
COP (declared)	COP _C	3,60	

Parameters at part load and ambient temperature 5°C

Capacity (declared)	P _D	12,33	kW
Power Input (declared)	D _D	2,55	kW
COP (declared)	COP _D	4,83	

Parameters at full load and ambient temperature 43°C

Capacity	P ₃	7,50	kW
Power Input	D ₃	4,76	kW
COP	COP ₃	1,58	

Other items

Capacity control		Fixed	
Degradation coefficient	Cds	0.25	

Contact details

Emerson Climate Technologies - European Headquarters - Pascalstrasse 65 - 52076 Aachen, Germany
 Phone: +49 (0) 2408 929 0 - Fax: +49 (0) 2408 929 570 - Internet: www.emersonclimate.eu